1) General information

Thank you for choosing an OSMA product.

- This operating manual was originally written for German speaking countries and users and has been translated from the German into English.
- Detailed technical information can be found under paragragh 2)
- The appliance must not be exposed to extreme heat , open flames or sparks as this can cause damage to electrical parts, insulating materials and electrical wiring.
- The appliance should not be allowed to come into contact with concentrated acids as this could lead to the disintegration of plastic casings or cause dangerous metal corrosion. If necessary, affected parts should be replaced with original spare parts as soon as possible.
- When in operation the ambient air temperature should be between 5℃ and 25℃. Under no circumstances should this temperature exceed 25℃.

1.1) Correct and intended use of the product

The OSMA – modular and mobile drying station is intended solely for the purpose of drying heavy duty and water-repellent protective clothing after use.
In the case of improper handling or misuse of this product the manufacturer`s guarantee automatically loses its validity.
As the fabric of the clothing to be dried is not known to OSMA, the OSMA Company cannot undertake to guarantee for any changes which may occur in the fabric whilst being treated.

1.2) Guarantee information

OSMA is not responsible for damages caused by false usage or improper handling. OSMA does not accept liability to third persons.
Changes to components or elements without the manufacturer`s consent and incorrect installation not in accordance with the manufacturer`s instructions will lead to loss of the guarantee.

1.3) Directives

The OSMA – modular and mobile drying station has been manufactured according to European and German standards, laws, regulations and guidelines. However when installing the product the specific local or national electro-technical regulations applicable to the country in question must be complied with.

2) Technical data

Type: Modular and mobile drying station for drying the insides of heavy- duty, water-repellent protective clothing after use.

Dimensions of Fireman
width/depth/height in mm:
max.3620/810/2000 (for 6 modules)

Warm air blower :
Wattage: max. 1200 Watt

Voltage/Frequency: 230 volts/~ Hz

Description: OSMA –modular and mobile drying station made of high grade V²A steel for 3 to 6 pieces of clothing. Suitable for 2-piece suits, jackets or trousers, positioned lengthwise.
Ready to plug into 230 volts.

3.) Installation

OSMA drying systems are supplied ready to plug into an energy supply of 230V/50Hz.

1. Set up the modular and mobile drying station in a horizontal position.
2. Brake the wheels (at least one)
3. Plug the unit directly into the electricity supply 230 volts, 50~Hz. Do not interfere with supply to the mains in any way!

4) Operation

1. Pull the work clothes and heavy-duty protective clothing fully over the jacket and trouser hangers intended for the purpose.
2. Turn on the warm air blower. Drying time is approx. 120-180 minutes. Warm air blower can also be turned on during the wash cycle.
3. The upper ends of the washing lances are rounded so that chemical suits can remain hung up for a longer period of time without adverse effect (no damage to boots or gloves)

Removal:

4. Repeat the above steps in opposite order.
5. Do not step on the appliance when removing clothing!

4) Transport and storage

The appliance should be stored in the wooden crate provided.
During transport it must be secured from dislocation and shifting and protected from adverse weather conditions.

If the unit cannot be installed directly after delivery it should be stored in a clean, dry place and protected against damage, dirt and moisture. The wooden crate is not weather-proof.

6) Service manual
Rectifying faults

The OSMA Modular and Mobile Drying Station FIREMAN is maintenance free.

Should however faults or problems occur with the product, please call your local specialist dealer.
The product is guaranteed for 2 years.

Attention:
Never attempt to open the electrical appliance alone! Repairs may only be carried out by trained and qualified service staff!

6) Disposal / Taking out of operation.

The parts of the Modular and Mobile Drying Station **Fireman** can be recycled when professionally disposed of and are therefore environmentally compliant.
Details of disposal and recycling are shown in the table below:

Product	Materials	Disposal
steel - construction motors screws etc.	metals	separating recycling by smelting down
protective caps casings covers	plastics	recycling burning or disposal in special dumbs
cables casings plugs etc.	rubber, PVC, silicon, polychlorophen	separating materials reycling
electronic parts	plastics, metals, electrolytes	Special disposal in accordance with locally authorized directives

Varnished and painted parts should be recycled according to the materials used or disposed of in accordance with locally authorized directives.

<u>Packing regulation:</u>
ARA licence no. 13068
Non liability agreement
for electrical appliances: ERA 50558

OSMA®

Operating manual for

OSMA – MODULAR and MOBILE DRYING STATION
for heavy duty and water-repellent protective clothing

Type Fireman